

XAllocSizeHints, XSetWMNormalHints, XGetWMNormalHints, XSetWMSizeHints, XGetWMSizeHints, XSizeHints – allocate size hints structure and set or read a window's **WM_NORMAL_HINTS** property

XSizeHints *XAllocSizeHints()

void XSetWMNormalHints(*display*, *w*, *hints*)

Display **display*;
Window *w*;
XSizeHints **hints*;

Status XGetWMNormalHints(*display*, *w*, *hints_return*, *supplied_return*)

Display **display*;
Window *w*;
XSizeHints **hints_return*;
long **supplied_return*;

void XSetWMSizeHints(*display*, *w*, *hints*, *property*)

Display **display*;
Window *w*;
XSizeHints **hints*;
Atom *property*;

Status XGetWMSizeHints(*display*, *w*, *hints_return*, *supplied_return*, *property*)

Display **display*;
Window *w*;
XSizeHints **hints_return*;
long **supplied_return*;
Atom *property*;

display Specifies the connection to the X server.
hints Specifies the size hints for the window in its normal state.
hints Specifies the **XSizeHints** structure to be used.
hints_return Returns the size hints for the window in its normal state.
property Specifies the property name.
supplied_return Returns the hints that were supplied by the user.
w Specifies the window.

The **XAllocSizeHints** function allocates and returns a pointer to a **XSizeHints** structure. Note that all fields in the **XSizeHints** structure are initially set to zero. If insufficient memory is available, **XAllocSizeHints** returns NULL. To free the memory allocated to this structure, use **XFree**.

The **XSetWMNormalHints** function replaces the size hints for the **WM_NORMAL_HINTS** property on the specified window. If the property does not already exist, **XSetWMNormalHints** sets the size hints for the **WM_NORMAL_HINTS** property on the specified window. The property is stored with a type of **WM_SIZE_HINTS** and a format of 32.

XSetWMNormalHints can generate **BadAlloc** and **BadWindow** errors.

The **XGetWMNormalHints** function returns the size hints stored in the **WM_NORMAL_HINTS** property on the specified window. If the property is of type **WM_SIZE_HINTS**, is of format 32, and is long enough to contain either an old (pre-ICCCM) or new size hints structure, **XGetWMNormalHints** sets the various fields of the **XSizeHints** structure, sets the *supplied_return* argument to the list of fields that were supplied by the user (whether or not they contained defined values), and returns a nonzero status. Otherwise, it returns a zero status.

If **XGetWMNormalHints** returns successfully and a pre-ICCCM size hints property is read, the *supplied_return* argument will contain the following bits:

(USPosition|USSize|PPosition|PSize|PMinSize|
PMaxSize|PResizeInc|PAspect)

If the property is large enough to contain the base size and window gravity fields as well, the supplied_return argument will also contain the following bits:

PBaseSize|PWinGravity

XGetWMNormalHints can generate a **PN BadWindow** error.

The **XSetWMSizeHints** function replaces the size hints for the specified property on the named window. If the specified property does not already exist, **XSetWMSizeHints** sets the size hints for the specified property on the named window. The property is stored with a type of **WM_SIZE_HINTS** and a format of 32. To set a window's normal size hints, you can use the **XSetWMNormalHints** function.

XSetWMSizeHints can generate **BadAlloc**, **BadAtom**, and **BadWindow** errors.

The **XGetWMSizeHints** function returns the size hints stored in the specified property on the named window. If the property is of type **WM_SIZE_HINTS**, is of format 32, and is long enough to contain either an old (pre-ICCCM) or new size hints structure, **XGetWMSizeHints** sets the various fields of the **XSizeHints** structure, sets the supplied_return argument to the list of fields that were supplied by the user (whether or not they contained defined values), and returns a nonzero status. Otherwise, it returns a zero status. To get a window's normal size hints, you can use the **XGetWMNormalHints** function.

If **XGetWMSizeHints** returns successfully and a pre-ICCCM size hints property is read, the supplied_return argument will contain the following bits:

(USPosition|USSize|PPosition|PSize|PMinSize|
PMaxSize|PResizeInc|PAspect)

If the property is large enough to contain the base size and window gravity fields as well, the supplied_return argument will also contain the following bits:

PBaseSize|PWinGravity

XGetWMSizeHints can generate **BadAtom** and **BadWindow** errors.

WM_NORMAL_HINTS Size hints for a window in its normal state. The C type of this property is **XSizeHints**.

The **XSizeHints** structure contains:

/* Size hints mask bits */

```
lw(.5i) lw(1.1i) lw(1.5i) lw(3.1i). T{ #define T} T{ USPosition T} T{ (1L << 0) T} T{ /* user
specified x, y */ T} T{ #define T} T{ USSize T} T{ (1L << 1) T} T{ /* user specified width,
height */ T} T{ #define T} T{ PPosition T} T{ (1L << 2) T} T{ /* program specified position */
T} T{ #define T} T{ PSize T} T{ (1L << 3) T} T{ /* program specified size */ T} T{ #define
T} T{ PMinSize T} T{ (1L << 4) T} T{ /* program specified minimum size */ T} T{ #define
T} T{ PMaxSize T} T{ (1L << 5) T} T{ /* program specified maximum size */ T} T{ #define
T} T{ PResizeInc T} T{ (1L << 6) T} T{ /* program specified resize increments */ T} T{ #define
T} T{ PAspect T} T{ (1L << 7) T} T{ /* program specified min and max aspect ratios */ T} T{
#define T} T{ PBaseSize T} T{ (1L << 8) T} T{ #define T} T{ PWinGravity T} T{ (1L <<
9) T} T{ #define T} T{ PAllHints T} T{ (PPosition|PSize|
PMinSize|PMaxSize|
PResizeInc|PAspect) T} T{ T}
```

/* Values */

typedef struct {

```
long flags;                /* marks which fields in this structure are defined */
int x, y;                  /* Obsolete */
int width, height;        /* Obsolete */
int min_width, min_height;
int max_width, max_height;
int width_inc, height_inc;
struct {
    int x;                  /* numerator */
    int y;                  /* denominator */
} min_aspect, max_aspect;
int base_width, base_height;
int win_gravity;
/* this structure may be extended in the future */
} XSizeHints;
```

The `x`, `y`, `width`, and `height` members are now obsolete and are left solely for compatibility reasons. The `min_width` and `min_height` members specify the minimum window size that still allows the application to be useful. The `max_width` and `max_height` members specify the maximum window size. The `width_inc` and `height_inc` members define an arithmetic progression of sizes (minimum to maximum) into which the window prefers to be resized. The `min_aspect` and `max_aspect` members are expressed as ratios of `x` and `y`, and they allow an application to specify the range of aspect ratios it prefers. The `base_width` and `base_height` members define the desired size of the window. The window manager will interpret the position of the window and its border width to position the point of the outer rectangle of the overall window specified by the `win_gravity` member. The outer rectangle of the window includes any borders or decorations supplied by the window manager. In other words, if the window manager decides to place the window where the client asked, the position on the parent window's border named by the `win_gravity` will be placed where the client window would have been placed in the absence of a window manager.

Note that use of the **PAIHints** macro is highly discouraged.

BadAlloc The server failed to allocate the requested resource or server memory. **BadAtom** A value for an Atom argument does not name a defined Atom. **BadWindow** A value for a Window argument does not name a defined Window.

XAllocClassHint(3X11), **XAllocIconSize(3X11)**, **XAllocWMHints(3X11)**, **XFree(3X11)**,
XSetCommand(3X11), **XSetTransientForHint(3X11)**, **XSetTextProperty(3X11)**,
XSetWMClientMachine(3X11), **XSetWMColormapWindows(3X11)**, **XSetWMIconName(3X11)**,
XSetWMName(3X11), **XSetWMProperties(3X11)**, **XSetWMProtocols(3X11)**,
XStringListToTextProperty(3X11)

Xlib – C Language X Interface