

XtErrorMsg, XtSetErrorHandler, XtWarningMsg, XtSetWarningMsgHandler – high-level error handlers

```
void XtErrorMsg(name, type, class, default, params, num_params)
    String name;
    String type;
    String class;
    String default;
    String *params;
    Cardinal *num_params;
void XtSetErrorHandler(msg_handler)
    XtErrorHandler msg_handler;
void XtSetWarningMsgHandler(msg_handler)
    XtErrorHandler msg_handler;
void XtWarningMsg(name, type, class, default, params, num_params)
    String name;
    String type;
    String class;
    String default;
    String *params;
    Cardinal *num_params;
```

<i>class</i>	Specifies the resource class.
<i>default</i>	Specifies the default message to use.
<i>name</i>	Specifies the general kind of error.
<i>type</i>	Specifies the detailed name of the error.
<i>msg_handler</i>	Specifies the new fatal error procedure, which should not return or the nonfatal error procedure, which usually returns.
<i>num_params</i>	Specifies the number of values in the parameter list.
<i>params</i>	Specifies a pointer to a list of values to be stored in the message.

The **XtErrorMsg** function has been superceded by **XtAppErrorMsg**.

The **XtSetErrorHandler** function has been superceded by **XtAppSetErrorHandler**.

The **XtSetWarningMsgHandler** function has been superceded by **XtAppSetWarningMsgHandler**.

The **XtWarningMsg** function has been superceded by **XtAppWarningMsg**