

DRM-1804X SPECIFICATIONS

Number of Disc	18 discs (3×6 disc magazine)
Media Type	CD-ROM, CD-Audio CD-ROM XA Mode 2, Form 1 and 2
Media Diameter	120 mm
Interface	SCSI-2
Block Size	2048/512 Byte (selectable)
Data Transfer Rate	614/153.4 kilobytes/Sec (Sustained) 4.2 MBytes/Sec (Burst)
Access Time	300 msec (1/3 stroke) 450 msec (full stroke)
Disc Change Time	less than 10 sec
Disc Start Up Time	less than 3 sec
Disc Spin Down Time	less than 2 sec
MTBF	20,000 hr.
Buffer Size	128 kilobytes
Regulatory Approval	UL, CSA, FCC Class B, VDE, TUV, SEMKO, BEAB, NEMKO, DEMKO, FIMKO, SEV

Audio Performance

Frequency Response	4 ~ 20,000 Hz \pm 2 dB
Total Harmonic Distortion	0.1% (Max)
Output Voltage	1.7V r.m.s. (line out) \pm 0.5V (10K Ω)

Physical Characteristics

Dimensions (W×H×D)	260×196.7×422.8 mm (10-1/4"×7-3/4"×16-5/8")
Weight (Net)	7.6Kg (16 lbs. 12 oz.)
Operating Voltage	100 ~ 240V 50/60 Hz
Rated Current Consumption	AC 120V 0.4A AC 240V 0.2A
Max. Current Consumption	AC 120V 0.5A AC 240V 0.2A


Environmental Conditions

Operating Temp	5 ~ 40°C
Operating Humidity (non-condensing)	5 ~ 90% RH
Storage Temp	-30 ~ 60°C
Storage Humidity (non-condensing)	5 ~ 90% RH


Accessories

DRM-A600	6 Disc Magazine
PCA-02	SCSI Daisy Chain Cable

DRM-1804X Dimensions



Configuration & Functions



•For details, contact address given below.

•Design and specifications subject to change without notice.

•LaserMemory and QUADRASPIN are trademarks of Pioneer Electronic Corporation.
All other product names are registered trademarks of their respective companies.