

XtFindFile – search for a file using substitutions in the path list

String XtFindFile(*path*, *substitutions*, *num_substitutions*, *predicate*)

String *path*;

Substitution *substitutions*;

Cardinal *num_substitutions*;

XtFilePredicate *predicate*;

path Specifies a path of file names, including substitution characters.
substitutions Specifies a list of substitutions to make into a path.
num_substitutions Specifies the number of substitutions passed in.
predicate Specifies a procedure to call to judge a potential file name, or NULL.

The *path* parameter specifies a string that consists of a series of potential file names delimited by colons. Within each name, the percent character specifies a string substitution selected by the following character. The character sequence “%:” specifies an embedded colon that is not a delimiter; the sequence is replaced by a single colon. The character sequence “%%” specifies a percent character that does not introduce a substitution; the sequence is replaced by a single percent character. If a percent character is followed by any other character, looks through the specified *substitutions* for that character in the *match* field and if found replaces the percent and match characters with the string in the corresponding *substitution* field. A *substitution* field entry of NULL is equivalent to a pointer to an empty string. If the operating system does not interpret multiple embedded name separators in the path (i.e., “/” in POSIX) the same way as a single separator, will collapse multiple separators into a single one after performing all string substitutions. Except for collapsing embedded separators, the contents of the string substitutions are not interpreted by and may therefore contain any operating-system-dependent characters, including additional name separators. Each resulting string is passed to the predicate procedure until a string is found for which the procedure returns this string is the return value for. If no string yields a return from the predicate, returns NULL.

If the *predicate* parameter is NULL, an internal procedure that checks if the file exists, is readable, and is not a directory will be used.

It is the responsibility of the caller to free the returned string using when it is no longer needed.

X Toolkit Intrinsic – C Language Interface

Xlib – C Language X Interface