

IBM ThinkPad® Dock

User's Guide



CAUTION -

Before installing this product, read the ThinkPad System Safety Booklet.

Note

Be sure to keep your proof of purchase, because it might be required for warranty services. (See Appendix A.)

First Edition (January 2000)

The following paragraph does not apply to the United Kingdom or any country where such provisions are inconsistent with local law:

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT ANY WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE LIMITED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimers or express or implied warranties in certain transactions; therefore, this statement may not apply to you.

This publication could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements or changes in the products or the programs described in this publication at any time.

It is possible that this publication may contain reference to, or information about, IBM products (machines and programs), programming, or services that are not announced in your country. Such references or information must not be construed to mean that IBM intends to announce such IBM products, programming, or services in your country.

Requests for technical information about IBM products should be made to your IBM authorized dealer or your IBM marketing representative.

© Copyright International Business Machines Corporation 2000. All rights reserved.

Note to U.S. Government Users — Documentation related to restricted rights — Use, duplication or disclosure is subject to restrictions set forth in GSA ADP Schedule Contract with IBM Corp.

Electrical safety notice



DANGER

Electric current from power, telephone, and network cables is hazardous. To avoid shock hazard, connect and disconnect cables as shown in the safety booklet when installing, moving., or operating the covers of this product or attached devices,



DANGER

Reduce the risk of fire and electric shock by always following basic safety precautions, including the following:

- Do not use your computer in or near water.
- During electrical storm:
 - Do not use the your computer with the telephone cable connection.
 - Do not connect the cable to or disconnect it from the telephone outlet of the wall.



DANGER

Before you install or remove the option, unplug the power cord.



Power is controlled by the power switch of the computer. In an emergency, turn off the power by unplugging the ThinkPad Dock power cord. The electrical outlet should be near the ThinkPad Dock and should be easily accessible.



To avoid a shock hazard:

- Do not connect or disconnect any cable or perform installation, maintenance, or reconfiguration of this product during an electoral storm
- The power cord must be connected to an outlet that has been properly wired and grounded according to your local wiring rules.

This equipment must have an earth ground.

Apparaten skall anslutas till jordat uttag när den ansluts till ett nätverk.

Jordet stikkontakt skal benyttes når apparatet tilkobles datanett.

Laite on liitettävä maadoitettuun pistorasiaan.

 Any equipment to which this product is attached must also be connected to an outlet that has been properly wired and grounded according to your local wiring rules.

CAUTION:

To reduce the risk of fire, use only No. 26 AWG or larger (thicker) telephone cable.

CAUTION:

Use the power cable that supplied with the ThinkPad Dock docking station.

Contents

lectrical safety notice	iii
Part 1. About the ThinkPad Dock	1-1
Part 2. Appendixes	2-1
ppendix A. Help and service information	2-2
Online technical support	
elephone technical support	
ppendix B. Warranty statements	2-3
ppendix C. Notices	2-13
rademarks	
lectronic emission notices	

Part 1. About the ThinkPad Dock

The ThinkPad Dock docking station has the Ultrabay $^{\text{\tiny TM}}$ 2000, a PCI slot, and PC Card slots.

After you attach your computer to the ThinkPad Dock docking station, you can use its connectors in place of those on the computer's, plus the following:

• Ultrabay 2000 slot

This bay accepts the same devices that are available in the Ultrabay 2000 slot of the computer, except the bay battery.

Note: Turn off the computer *before* you install a device in or from the Ultrabay 2000 slot of the ThinkPad Dock docking station. Do not insert or remove an Ultrabay 2000 device while the computer is on.

PCI slot


This slot accepts a short-size PCI card. Maximum length, 174 mm (6.9 in).

• PC Card slots

These slots are the same as those on the computer. For details, refer to the online information on your computer.

Notes:

- If you are using Windows 95, you can use only the lower USB connector of the ThinkPad Dock docking station.
- 2. Before attaching your computer to the ThinkPad Dock docking station, connect the power cord and the network cable (if you use the network) as follows:



For details about the ThinkPad Dock docking station, refer to the online information on your computer.