

**XtAppErrorMsg, XtAppSetErrorHandler, XtAppSetWarningMsgHandler, XtAppWarningMsg**  
– high-level error handlers

```
void XtAppErrorMsg(app_context, name, type, class, default, params, num_params)
    XtApplicationContext app_context;
    String name;
    String type;
    String class;
    String default;
    String *params;
    Cardinal *num_params;

void XtAppSetErrorHandler(app_context, msg_handler)
    XtApplicationContext app_context;
    XtErrorMsgHandler msg_handler;

void XtAppSetWarningMsgHandler(app_context, msg_handler)
    XtApplicationContext app_context;
    XtErrorMsgHandler msg_handler;

void XtAppWarningMsg(app_context, name, type, class, default, params, num_params)
    XtApplicationContext app_context;
    String name;
    String type;
    String class;
    String default;
    String *params;
    Cardinal *num_params;
```

<i>app_context</i>	Specifies the application context.
<i>class</i>	Specifies the resource class.
<i>default</i>	Specifies the default message to use.
<i>name</i>	Specifies the general kind of error.
<i>type</i>	Specifies the detailed name of the error.
<i>msg_handler</i>	Specifies the new fatal error procedure, which should not return or the nonfatal error procedure, which usually returns.
<i>num_params</i>	Specifies the number of values in the parameter list.
<i>params</i>	Specifies a pointer to a list of values to be stored in the message.

The **XtAppErrorMsg** function calls the high-level error handler and passes the specified information.

The **XtAppSetErrorHandler** function registers the specified procedure, which is called when a fatal error occurs.

The **XtAppSetWarningMsgHandler** function registers the specified procedure, which is called when a nonfatal error condition occurs.

The **XtAppWarningMsg** function calls the high-level error handler and passes the specified information.

**XtAppGetErrorHandlerDatabase(3Xt), XtAppError(3Xt)**

*X Toolkit Intrinsics – C Language Interface*

*Xlib – C Language X Interface*