

XtAppGetErrorHandler, XtAppGetErrorHandlerText – obtain error database

```
XrmDatabase *XtAppGetErrorHandler(app_context)
    XtAppContext app_context;
void XtAppGetErrorHandlerText(app_context, name, type, class, default, buffer_return, nbytes, database)
    XtAppContext app_context;
    char *name, *type, *class;
    char *default;
    char *buffer_return;
    int nbytes;
    XrmDatabase database;
```

<i>app_context</i>	Specifies the application context.
<i>buffer_return</i>	Specifies the buffer into which the error message is to be returned.
<i>class</i>	Specifies the resource class of the error message.
<i>database</i>	Specifies the name of the alternative database that is to be used or NULL if the application's database is to be used.
<i>default</i>	Specifies the default message to use.
<i>name</i>	
<i>type</i>	Specifies the name and type that are concatenated to form the resource name of the error message.
<i>nbytes</i>	Specifies the size of the buffer in bytes.

The **XtAppGetErrorHandler** function returns the address of the error database. The Intrinsics do a lazy binding of the error database and do not merge in the database file until the first call to **XtAppGetErrorHandlerText**.

The **XtAppGetErrorHandlerText** returns the appropriate message from the error database or returns the specified default message if one is not found in the error database.

XtAppError(3Xt), XtAppErrorMsg(3Xt)

X Toolkit Intrinsics – C Language Interface

Xlib – C Language X Interface