



## Personal System/2 Models 55 SX and 55 LS

### Powerful performance at a practical price

Boost productivity in your own work and on your network with Personal System/2® Models 55 SX and 55 LS. Built around Intel386™ SX microprocessors, they support 32-bit applications for a practical price. And because they're based on Micro Channel® architecture, they make multitasking and multiuser applications practical, too.


These midline members of the PS/2® family now come with standard 4MB of expandable memory (twice as much as in the past). Beyond that standard, you have lots of ways to go. Choose an SX system with new, higher-capacity hard files—40 or 80 million bytes of disk storage. Select a medialess LS that's preconfigured for your Token-Ring or Ethernet LAN. Get built-in Video Graphics Array (VGA) graphics for business presentations and reports.

No matter which model you pick, superior quality and reliability are part of the package. You can count on smooth performance—at a reasonable cost.

### Model 55 SX and Model 55 LS at work

Here are some of the ways you can put the Model 55 SX or Model 55 LS to work for you:

- Process advanced 32-bit, 386-based applications without stretching your budget



- Support your pick of popular DOS programs with DOS 5.0—or do advanced multitasking with OS/2®
- Handle word processing files, work with a database, create an exciting presentation—even combine information from all three
- Share files, operating systems, programs, printers, plotters and other peripherals on a LAN

Feature	Benefit
<b>16 MHz i386™ SX microprocessor</b>	<ul style="list-style-type: none"> <li>• Delivers impressive speed and power for business applications</li> <li>• Supports 32-bit, 386 applications at an affordable price</li> </ul>
<b>Micro Channel architecture</b>	<ul style="list-style-type: none"> <li>• Provides efficient data paths for fast, reliable, balanced performance</li> <li>• Protects investment by providing a platform for future expansion and growth</li> </ul>
<b>Up to 8MB memory on the system board</b>	<ul style="list-style-type: none"> <li>• Gives you plenty of room and workspace without using an expansion slot</li> <li>• Lets you work with large amounts of data</li> </ul>
<b>Fixed disk drives</b>	<ul style="list-style-type: none"> <li>• Allow choice of 40 or 80MB—standard on SX models, optional on LS models</li> </ul>
<b>Available expansion slots</b>	<ul style="list-style-type: none"> <li>• Let you add more function</li> </ul>
<b>Built-in graphics capabilities</b>	<ul style="list-style-type: none"> <li>• VGA: Ensures crisp, clear graphics and text</li> </ul>
<b>Preconfigured, medialess system with remote program load</b>	<ul style="list-style-type: none"> <li>• Comes with Token-Ring or Ethernet preinstalled</li> <li>• Makes the Model 55 LS a network workstation that you can simply plug in</li> </ul>

### Model 55 SX

Power supply

4MB standard memory

Keyboard port

Pointing device port

Parallel port

Serial port

Display port


16-bit expansion slots

Fixed disk (40MB or 80MB)

1.44MB 3.5-inch diskette drive

i386 SX processor

i387™ SX math coprocessor  
(optional)



## Wide range of options<sup>1</sup>

	Part no.
<b>Storage devices</b>	
• 3.5" 1.44MB 1-inch High Diskette Drive	6451072
• 5.25" 1.2MB External Diskette Drive	4869002
• 5.25" 360KB External Diskette Drive	4869001
• 40MB Fixed Disk Drive <sup>2</sup>	6451047
• 80MB Fixed Disk Drive <sup>2</sup>	6451043
• External CD-ROM Drive	3510001
• 3.5" Rewritable Optical Drive	6450162
• 6157 Streaming Tape Drive (60MB, 150MB)	6157001/6157002
• 3363 External Optical Disk A11	68X7946
• 3363 External Optical Disk B01	63X4182
<b>Scanners</b>	
• 3117 Scanner	3117010
• 3118 Scanner	3118010/3118020
• 3119 PageScanner	94X2410
<b>Connectivity/communications</b>	
• Token-Ring Network Adapter A	69X8138
• Token-Ring Network 16/4 Adapter/A	16F1133
• Token-Ring Network 16/4 Trace and Performance Adapter/A	74F5130
• Adapter/A for Ethernet Networks	6451091
• Dual Async Adapter/A	6451013
• Multi-Protocol Adapter/A	6451003
• 3270 Connection	74F3465
• 300/1200/2400 Internal Modem/A	94X1755
• Leased Line Modem	26F1862
• System 36/38 W/S Emulation Adapter/A	69X6279
• System/370™ Channel Emulation Adapter/A	1674899
• Realtime Interface Co-Processor Multiport/2 and related features	09F1897 <sup>3</sup>
• Realtime Interface Co-Processor Portmaster Adapter/A and related features	53F2601 <sup>3</sup>
• X.25 Realtime Interface Co-Processor/2	16F1858
<b>Image graphics and multimedia</b>	
• XGA Display Adapter/A	75X5887
• Display Adapter 8514/A	1887972
• Image Adapter/A series	44F9914 <sup>2</sup>
• Audio Capture/Playback Adapter/A	34F2784
• Video Capture Adapter/A	34F2785
• Enhanced M-Motion Video Adapter/A	95F1091
<b>Other features</b>	
• Micro Channel SCSI Adapter	6451109
• Micro Channel SCSI Adapter with Cache	6451110
• PS/2 Mouse	6450350
• Screen Reader™	6450602

## Memory matrix table

Memory on system board	All models
Standard memory	4MB
Maximum memory	8MB
System board memory expansion kits (part number)	1MB (6450603) 2MB (6450604) 4MB (87F9977)
Number of memory kits that can be added on system board	1
Memory configurations possible on system board	4MB, 5MB, 6MB, 8MB
<b>Memory options (cards)</b>	
Memory expansion card size (part number) and capacity range	2MB (6540609) 2-8MB
Memory kits to upgrade card	1MB (6450603) 2MB (6450604)
Maximum number of memory kits that can be added to each memory card	3
Maximum number of memory cards/system	2
Maximum system memory	16MB

## Why PS/2?

There are some of the reasons why PS/2 stands out as the best solution for your business needs.

**Technological leadership** through Micro Channel architecture, integrated construction and advanced design (by combining Very Large-Scale Integration and Surface Mount Technology), and optional SCSI support for large data storage.

**Extensive communications capabilities** through a wide range of connectivity options—provide concurrent support for intelligent communications adapters and coprocessors, thanks to Micro Channel architecture.

**Compatibility and expandability** to protect your investment since the PS/2s you use today work with existing products and programs and with those you'll need tomorrow.

**Service and support** that provide you with everything from fast parts delivery and on-site services to system planning to 24-hour phone support—all at a competitive price.

**Business Partners** who enhance PS/2 capabilities by helping customers choose, customize and configure hardware and software to meet a range of needs.

**Quality and reliability** that ensure PS/2s are built to perform smoothly and dependably year after year.

IBM, Personal System/2, Micro Channel, PS/2, Proprinter, Quickwriter, Quietwriter, Operating System/2, and AIX are registered trademarks of International Business Machines Corporation. Novell and NetWare are registered trademarks of Novell Inc. PageMaker is a registered trademark of Aldus Corporation. Screen/370, ScreenReader and ExecJet are trademarks of International Business Machines Corporation. Intel386, i386 and i387 are trademarks of Intel Corporation. Options listed may require other features for desired function or for installation. Optional on Models 8555-LT0 and LE0 only. There is more than one part number for this type of option depending on the amount of on-card memory and/or other functions desired. 4MB of this memory is reserved for hardware use. Supported by PS/2 Image Adapter/A series. Future release of OS/2 LAN Server will provide remote IPL support in a Token-Ring Network and both DOS and OS/2 remote IPL support in an Ethernet network.

This document was created on an IBM Personal System/2 Model 70 386 with Aldus PageMaker®4.0 desktop publishing software.

## IBM Personal System/2 Model 55 SX and Model 55 LS at a glance

Machine numbers	8555-041, 081	8555-LT0, LE0
<b>Microprocessor</b>		
Standard	80386 SX	80386 SX
Clock speed	16 MHz	16 MHz
Wait states	0-2	0-2
Optional	80387 SX	80387 SX
Clock speed	16 MHz	16 MHz
Part number	27F4676	27F4676
<b>Bus architecture</b>		
Data path	Micro Channel	Micro Channel
	16-bit	16-bit
<b>Memory (RAM)*</b>		
Standard	4MB (85ns)	4MB (85ns)
Maximum on system board	8MB	8MB
System maximum	16MB	16MB
<b>Integrated functions</b>		
	VGA and display port, serial port, parallel port, pointing device port, keyboard port, disk and diskette controllers, clock/calendar, security password feature; Token-Ring 16/4 Adapter/A with RPL feature (LT0), Ethernet Adapter (LE0)	
<b>Available expansion slots</b>		
	Three 16-bit	Two 16-bit
<b>Diskette storage (internal)</b>		
Standard (3.5-inch)	1.44MB	—
Optional	—	One 1.44MB
<b>Fixed disk storage</b>		
Standard	041: 40MB (17ms) 081: 80MB (16ms)	—
Optional	—	40MB (17ms), 80MB (16ms)
<b>Display modes</b>		
Text	VGA (includes all EGA, CGA and MCGA modes)	
Graphics	360 or 720 x 400; 9 x 16 pel character matrix; 80 columns x 25 rows; up to 16 colors palette of 256,000 colors or 64 gray shades; 640 x 480 x 16 colors or 16 gray shades; palette of 256,000 colors or 64 gray shades	
Optional graphics	Expanded graphics modes, including 1,024 x 768 x 256 colors are supported via the optional PS/2 Display Adapter 8514/A or XGA Display Adapter/A and related features; higher-resolution modes are supported by the PS/2 Image Adapter/A series	
<b>Supported displays</b>		
	IBM Personal System/2 Color Displays 8512, 8513, 8514, 8515 and 8516; IBM Personal System/2 Monochrome Displays 8504, 8506, 8507 and 8508*	
<b>Supported printers/plotters</b>		
	IBM Proprinter® family, IBM Quickwriter®, IBM Quietwriter® III, IBM ExecJet,™ IBM LaserPrinter family, IBM Page Printer 3812/3816, IBM 618X and 737X Color Plotters	
<b>Keyboard</b>		
	101 keys, including 12 function keys, 3 lighted mode indicators; 6-foot coiled cable	
<b>Power supply</b>		
	90-watt worldwide, manual switching	
<b>Operating systems</b>		
	041, 081: DOS 3.3 or higher, IBM Operating System/2® Standard or Extended Edition 1.2 or 1.3, AIX® Personal System/2 1.2 (081 only); LT0: DOS 3.3 or higher client support provided by an Operating System/2 server using OS/2 Extended Edition 1.2 or 1.3 and OS/2 LAN Server 1.2 or 1.3,* or by a DOS server using DOS 3.3 or higher, PC LAN Program 1.33, and LAN Support Program 1.2; LE0: DOS client support of DOS 3.3 or higher provided by Novell NetWare® 286 or 386	
<b>Size</b>		
	Approx. 4.0"H x 16.0"W x 15.6"D (102mm x 406mm x 397mm); 19.0 lbs (8.6 kg)	
<b>Warranty</b>		
	One-year limited warranty	



©International Business Machines Corporation 1991

IBM United States  
Department ZW1  
1133 Westchester Avenue  
White Plains, NY 10604

Printed in the United States of America  
6-91  
All Rights Reserved

References in this publication to IBM products or services do not imply that IBM intends to make them available outside the United States.



G221-3126-00